

SE 554 Memosens pH Sensor

Low-maintenance sensor for demanding process application in the chemical industry, digital, with Memosens technology

High accuracy, stability, rapidness, and a long life cycle are achieved by the special design. Through 2 open junctions, the reference system is in direct contact with the measured medium. There is hardly any risk of contamination or blocking of the junction. The high content and special distribution of potassium chloride in the polymer reduces measurement disturbances which could be caused by liquid junction potentials.

Applications

Industrial applications, dyes, precipitation reactions, polluted media


Facts

- Perfect galvanic isolation thanks to Memosens technology
- No influence of humidity in the connector
- Precalibration in the lab
- Digital data transfer
- Integrated sensor diagnostics
- Low maintenance, no refilling of electrolyte
- Integrated temperature detector
- Open junctions, no blocking
- Alpha glass, medium impedance, universal glass, fluoride resistant

Specifications

pH:	0 ... 14
Temperature:	0 ... 130 °C
Pressure, relative:	0 ... 10 bar
Temperature detector:	NTC 30 kohms
Sensor material:	Alpha glass
Reference system:	Ag/AgCl, polymeric electrolyte
Junction:	Hole (2 x)
Length:	120 mm / 225 mm / 325 mm / 425 mm
Process adaptation:	PG 13.5
Sensor connector:	Memosens
ATEX marking:	II 1 G Ex ia IIC T3/T4/T6
FM marking:	IS for Class I, Division 1, Groups A, B, C, D; Class I, Zone 0, AEx/Ex ia IIC T6 ... T4 NIFW for Class I, Division 2, Groups A, B, C, D; Class I, Zone 2, IIC T6 ... T4

Dimension Drawing



All dimensions in mm

SE 554 Memosens pH Sensor

Product line

Sensor	Length	Order No.
SE 554 pH sensor	120 mm	SE 554X/1-NMSN
	225 mm	SE 554X/2-NMSN
	325 mm	SE 554X/3-NMSN
	425 mm	SE 554X/4-NMSN

Accessories	Length	Order No.
Memosens cable	3 m	CA/MS-003NAA
	5 m	CA/MS-005NAA
	10 m	CA/MS-010NAA
	20 m*)	CA/MS-020NAA
Memosens cable, Ex	3 m	CA/MS-003XAA
	5 m	CA/MS-005XAA
	10 m	CA/MS-010XAA
	20 m*)	CA/MS-020XAA

CaliMat Buffer Solutions (20 °C)	Quantity	Order No.
pH value 2,00 ± 0,02	250 ml	CS-P0200/250
	250 ml	CS-P0400/250
	1000 ml	CS-P0400/1000
	3000 ml	CS-P0400/3000
pH value 4,00 ± 0,02	250 ml	CS-P0700/250
	1000 ml	CS-P0700/1000
	3000 ml	CS-P0700/3000
pH value 7,00 ± 0,02	250 ml	CS-P0900/250
	1000 ml	CS-P0900/1000
	3000 ml	CS-P0900/3000
pH value 9,00 ± 0,02	250 ml	CS-P1200/250
	1000 ml	CS-P1200/1000
	3000 ml	CS-P1200/3000
pH value 12,00 ± 0,05	250 ml	CS-P1200/250

MemoSuite		Order No.
Management software for Memosens sensors	Basic version (calibration)	SW-MS1400-B
	Advanced version (calibration, diagnostics, documentation)	SW-MS1400-A

*) Greater lengths on request